

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 2 E.

CHAINS	<p>Soil; mountain loam, 3rd rate.</p> <p>Timber; hemlock, fir, cedar, and pine.</p> <p>Undergrowth; vinemaple, and rhododendron.</p>
40.00	<p>S.89*59'E., on a random line bet. secs. 3 and 10</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.08	<p>Intersect N. and S. line 33 lks. N. of the cor. of secs. 2,3, 10, and 11, hereinbefore described</p>
	<p>Thence</p>
	<p>N.89*45'W., on true line bet. secs. 3 and 10</p>
	<p>Along N. slope, through heavy timber and dense undergrowth.</p>
1.80	<p>Creek, 1 lk. wide, course NE., asc. 60 ft. over NE. slope.</p>
8.10	<p>Spur, slopes N., desc. 30 ft. over gradual NW. slope</p>
20.70	<p>Creek, 3 lks. wide, course N., asc. 84 ft. over NE. slope.</p>
26.30	<p>Along broken gradual N. slope.</p>
40.44	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, with brass cap marked</p>
	<p>$\frac{1}{4} \frac{S3}{S10}$</p>
	<p>1928</p>
	<p>from which,</p> <p>A hemlock, 16 ins. diam., bears N.42*E., 64 lks. dist., marked $\frac{1}{4}$ S 3 B T</p>
	<p>A cedar, 8 ins. diam., bears S.17*E., 14 lks. dist., marked $\frac{1}{4}$ S 10 B T</p>
	<p>Desc. 43 ft. over NW. slope.</p>
41.80	<p>Creek, 2 lks. wide, course N.,</p>
48.60	<p>Creek, 1 lk. wide, course N., asc. 60 ft. over NE. slope.</p>
51.50	<p>Spur, N., along broken N. slope.</p>