

Subdivisions of T. 25 S., R. 2 E;

CHAINS

- 33.30 Creek, 2 lks. wide, course W.
- 35.40 Spur, slopes SW.,
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 19 and 20, with brass cap marked

$\frac{1}{4}$
S19 | S20
1928

from which,

- A fir, 14 ins. diam., bears N.77*E., 29 lks. dist., marked $\frac{1}{4}$ S 20 B T
- A fir, 16 ins. diam., bears N.37*W., 20 lks. dist., marked $\frac{1}{4}$ S 19 B T

Desc. 138 ft. over NW. slope.

- 45.70 Creek, 1 lk. wide, course NW., asc. 50 ft. over broken W. slope.
- 48.00 Creek, 2 lks. wide, course W.,
- 61.00 Creek, 1 lk. wide, course SW.,
- 63.50 Draw, course SW., asc. 130 ft. over SW. slope.
- 72.50 Spur, slopes SE., desc. 100 ft. over NW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground, for cor. of secs. 17, 18, 19, and 20, with brass cap marked

T25S | R2E
S18 | S17

S19 | S20
1928

from which,

- A fir, 24 ins. diam., bears N.61*E., 51 lks. dist., marked T 25 S R 2 E S 17 B T
- A maple, 9 ins. diam., bears S.5*E., 66 lks. dist., marked T 25 S R 2 E S 20 B T
- A fir, 10 ins. diam., bears S.56W., 59 lks. dist., marked T 25 S R 2 E S 19 B T
- A chinquapin, 8 ins. diam., bears N.46W., 73 lks.