

County Surveyor's Record, Douglas County, Oregon

South Boundary, T. 24 S., R. 3 E.
As Surveyed by John G. Collins, U.S. Cadastral Engineer
Under Special Instructions, dated March 12, 1921

CHAINS

From the cor. of Tps. 24 and 25 S., R. 3 E. only,
hereinbefore described,

West, on a true line, on S. Bdy. of Sec. 36.

Asc. E. slope, through heavy timber and dense undergrowth

2.60 Spur slopes S.60°E.; continue asc. along S. slope.

22.50 Dry ravine, course S.70°E.; asc. NE. slope.

31.75 Staley Ridge trail, bears N. and S.

32.80 Top of Staley Ridge, bears NW. and SE., 1200 ft. above
Tp. cor.

Desc. 250 ft. over steep SW. slope.

39.45 Mid point on S. Bdy. of sec. 36, determined as herein-
after set forth.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with
brass cap marked

$\frac{1}{4}$ S36

1926

from which

A fir, 36 ins. diam., bears N.56°E., 113 lks.
dist., marked $\frac{1}{4}$ S 36 B T

A fir, 8 ins. diam., bears N.80°W., 134 lks.
dist., marked $\frac{1}{4}$ S 36 B T

Thence along S. slope.

41.46 To top of rocky bluff, facing W., 100 ft. high.

From this point the line descends over bluffs on W. slope
and thence over bluffs on broken S. slope.

To determine the distance, I leave

a flag at this point and proceed

to the point of intersection of

the S. bdy. and a line projected

South from the south 1/16 sec. cor.

bet. secs. 35 and 36, determined as

hereinafter set forth. From the point