

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S., R. 3 E.

CHAINS

57.70 Coal Creek, 20 lks. wide, course N., 800 ft. below $\frac{1}{4}$ sec. cor.

Enter dense undergrowth, bears N. and S.

Asc. 760 ft. over E. slope.

77.75 Spur, slopes SE.; desc. 30 ft. over SW. slope

79.80 Point of intersection of line bet. secs. 34 and 35, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bed rock, surrounded by mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 34 and 35 only, with brass cap marked

T24S	R3E
S34	S35

1926

from which

A fir, 24 ins. diam., bears N.21°E., 77 lks. dist., marked T 24 S R 3 E S 35 B T

A fir, 18 ins. diam., bears N.47°W., 43 lks. dist., marked T 24 S R 3 E S 34 B T

Land, mountainous.

Soil, rocky; 3rd and 4th rate.

Timber; fir, pine, hemlock, and cedar.

Undergrowth; vinemapple, rhododendron, hazel, willow, and alder.

West, on S. bdy. of sec. 34

Desc. 45 ft. over SW. slope, through heavy timber and dense undergrowth.

1.88 Dry ravine, course SE.; asc. NE. slope.

7.96 To foot of bluff, facing NE.

Offset North, 2.11 chs.

Thence