

South Boundary of T. 24 S., R. 3 E.

CHAINS

West, on offset line, continuing measurement.  
 16.84 To foot of impassable bluff, facing NE.  
 Offset North, 1.59 chs.  
 Thence  
 West, on offset line, continuing measurement.  
 20.40 Offset North, 0.66 chs., to pass bluff.  
 Thence  
 West, on offset line, continuing measurement.  
 24.94 Offset South, 4.36 chs. to true line.  
 Thence  
 West on true line, continuing measurement.  
 39.45 Foot of bluff, 150 ft. high, faces E.  
 39.80 Top of bluff, 750 ft. above sec. cor.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
 the ground, for  $\frac{1}{4}$  sec. cor. of sec. 34 only, with  
 brass cap marked.  
 $\frac{1}{4}$  S34  
1926  
 from which  
 A fir, 36 ins. diam., bears N.2 $\frac{1}{2}$ °E., 258 lks.  
 dist., marked  $\frac{1}{4}$  S 34 B T.  
 A fir, 30 ins. diam., bears N.25°W., 223 lks.  
 dist., marked  $\frac{1}{4}$  S 34 B T.  
 42.00 Foot of bluff, 250 ft. high, faces E.  
 46.50 Foot of bluff, 100 ft. high, faces E.  
 48.40 Top of spur, slopes SE.; thence along S. slope.  
 71.80 Leave heavy timber and dense undergrowth, enter open  
 meadow, bears NW. and SE.  
 76.00 Summit of Calappa Mtns., divide between the Willamette  
 and Umpqua rivers, bears NW. and SE., 560 ft. above  
 $\frac{1}{4}$  sec. cor.  
 Desc. gradual W. slope