

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S., R. 3 E.

CHAINS

A hemlock, 10 ins. diam., bears N.56°E., 45 lks. dist., marked $\frac{1}{4}$ S 32 B T.

A hemlock, 12 ins. diam., bears N.61°W., 53 lks. dist., marked $\frac{1}{4}$ S 32 B T.

Continue asc., 75 ft. to

44.00 Thence over nearly level bench.

51.80 Asc. 175 ft. over E. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 31 and 32 only, with brass cap marked

T24S	R3E
S31	S32
1926	

from which

A fir, 12 ins. diam., bears N.32°E., 33 lks. dist., marked T 24 S R 3 E S 32 B T.

A fir, 16 ins. diam., bears N.51°W., 55 lks. dist., marked T 24 S R 3 E S 31 B T.

Land, mountainous.

Soil, rocky clay loam; 2nd rate.

Timber, fir, hemlock, cedar, and pine.

Undergrowth, vine maple, rhododendron, hazel, alder, and yew.

West, on S. bdy. of sec. 31

Asc. SE. slope, through heavy timber and dense undergrowth.

20.70 Leave timber and undergrowth, enter N. side of open meadow, about 10 chs. wide, bears NW. and SE.

24.70 Leave open meadow, enter heavy timber and dense undergrowth, bears N. and S.

40.00 Top of spur ridge, bears N. and S., 680 ft. above sec. cor. Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bed rock, surrounded by a mound of stone, 3 ft. base, 2 ft high, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked