

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 3 E.

CHAINS

regular temp. $\frac{1}{4}$ sec. and sec. cors.; at 474.32 chs. intersect a line projected south from the cor. of Tps. 24 and 25 S., R. 3 E., as hereinafter determined. At point of intersection set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for the cor. of Tps. 25 S., Rs. 3 and 4 E., with brass cap mkd.

T25S	
R3E	R4E
S36	S31
<hr/>	
T25, SR4E	
S31	
1931	

from which

A hemlock, 16 ins. diam., bears N.45°E., 97 lks.

dist., mkd. T 25 S R 4 E S 31 B T

A fir, 12 ins. diam., bears N.43°W., 89 lks.

dist., mkd. T 25 S R 3 E S 36 B T

Thence

West, on true line on S. bdy. of sec. 36

Along N. slope, through heavy timber and dense undergrowth.

1.30 Creek, 5 lks, wide, course N.80°E., asc. 320 ft. along broken SE. slope to the $\frac{1}{4}$ sec. cor.

21.00 Spur, slopes S.,

24.60 Draw, drains S.,

28.90 Spur, slopes S.,

37.10 Same creek, 5 lks, wide, course S.60°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$ S36
<hr/>
1931

from which

A hemlock, 12 ins. diam., bears N.26°E., 19 lks.

dist., mkd. $\frac{1}{4}$ S 36 B T

A fir, 15 ins. diam., bears N.28°W., 63 lks.

dist., mkd. $\frac{1}{4}$ S 36 B T