

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 3 E.

CHAINS

Asc. 442 ft. over broken NE. slope, to cor.

56.20 Top of bluff, 100 ft. high, bears N.75°W., and S.75°E.

58.60 Same creek, course N.75°E., from W., thence asc. along
creek.

75.00 Junction of creek, 2 lks. wide, course S.20°E.

75.40 Leave creek, course E., from S.75°W.,

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for the cor. of secs. 35 and 36 only,
with brass cap mkd.

T25S	R3E
S35	S36
T25 ¹ / ₂ SR3E	
S36	
1931	

from which

A fir, 20 ins. diam., bears N.43°E., 77 lks.
dist., mkd. T 25 S R 3 E S 36 B TA fir, 20 ins., diam., bears N.13°W., 42 lks.
dist., mkd. T 25 S R 3 E S 35 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, hemlock, pine and yew.

Undergrowth; vinemaple, rhododendron, young fir and
hemlock, and hazel.

West, on true line on S. bdy. of sec. 35

Asc. 633 ft. over broken NE. slope to $\frac{1}{2}$ sec. cor.,
through heavy timber and medium undergrowth.

3.60 Spur, slopes N.,

3.90 Creek, 1 lk. wide, course N.,

11.90 Spur, slopes NE.

29.30 Same spur, slopes S.,

31.20 Draw, drains S., from N.85° W.,

35.20 Same draw, drains N.75°E.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in
the ground to bedrock, and in a mound of stone to top,
for $\frac{1}{2}$ sec. cor. of sec. 35 only, with brass cap mkd.