

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 3E.

CHAINS

West, on S. bdy. of sec. 33

Desc. 448 ft. over broken NW. slope, through heavy timber and medium undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 33 only, with brass cap mkd.

$\frac{1}{4}$  S33  
1931

from which

A fir, 46 ins. diam., bears N.60°E., 93 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T

A fir, 60 ins. diam., bears N.7°W., 77 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T

Desc. 38 ft. over NW. slope.

40.90 Creek, 7 lks. wide, course S.75°W., asc. 54 ft. over broken SE. slope.

43.90 Spur, slopes S.,

46.70 Draw, drains S.,

49.20 Spur, slopes SE.,

55.80 Spur, slopes S., desc. 293 ft. over SW. slope.

63.60 Draw, drains S.,

66.10 Spur, slopes S.,

73.70 Creek, 1 lk. wide, course S., along broken S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 32 and 33 only, with brass cap mkd.

T25S	R3E
S32	S33
T25SR3E	
S33	
1931	

from which

A fir, 36 ins. diam., bears N.14°E., 110 lks. dist., mkd. T 25 S R 3 E S 33 B T

A fir, 40 ins. diam., bears N.46°W., 65 lks. dist., mkd. T 25 S R 3 E S 32 B T