

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 3 E.

CHAINS

A hemlock, 18 ins. diam., bears N.77°E., 90 lks.

dist., mkd. T 25 S R 3 E S 32 B T

A fir, 26 ins. diam., bears N.45°W., 178 lks.

dist., mkd. T 25 S R 3 E S 31 B T

Land; mountainous.

Soil; rocky, 4th. rate.

Timber; fir, hemlock, pine, madrona, and yew.

Undergrowth; rhododendron, vine maple, and chinquapin.

West, on S. bdy. of sec. 31

Desc. 117 ft. over NW. slope, through heavy timber
and dense undergrowth.

4.80 Way trail, bears N. and S.,

5.90 Boulder Creek, 45 lks. wide, course S., asc. 421 ft.
over E. slope.

18.00 Spur, slopes S., desc. 161 ft. over SW. slope.

26.10 Draw, drains SE., asc. 245 ft. over E. slope.

31.30 Spur, slopes S., desc. 96 ft. over SW. slope.

35.40 Creek, 2 lks. wide, course S., asc. 236 ft. over E.
slope.40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{2}$ sec. cor. of sec. 31 only,
with brass cap mkd. $\frac{1}{2}$ S31
1931

from which

A fir, 12 ins. diam., bears N.3°E., 77 lks.

dist., mkd. $\frac{1}{2}$ S 31 B T

A fir, 38 ins. diam., bears N.18°W., 107 lks.

dist., mkd. $\frac{1}{2}$ S 31 B T

Asc. 97 ft. over E. slope.

43.20 Spur, slopes SW., desc. 419 ft. over broken SW. slope
to cor.