


County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R. 3 E.

CHAINS	
	<p>A fir, 48 ins. diam., bears N.48°E., 464 lks. dist., mkd. T 25 S R 4 E S 19 B T</p> <p>A fir, 28 ins. diam., bears N. 17°W., 360 lks. dist., mkd. T 25 S R 3 E S 24 B T</p> <p>No other trees available; raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land; mountainous.</p> <p>Soil; rocky, 4th. rate.</p> <p>Timber; fir, hemlock, pine, cedar, and yew.</p> <p>Undergrowth; vinemaple, chiquapin, manzanita, mountain laurel, rhododendron, hazel, and huckleberry</p>
	<p>North, bet. secs. 19 and 24</p> <p>Asc. 128 ft. over S. slope, over meadow.</p>
4.00	Enter heavy timber and medium undergrowth, bears E. and W.
5.60	Calapooya Mountains, divide bet. the North Umpqua and the Willamette rivers, bears E. and W., desc. 590 ft. over broken N. slope.
19.50	Draw, drains NE.,
21.40	Spur, slopes NE.,
28.60	Creek, 3 lks. wide, course N.70°E., along broken E. slope
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the 1/4 sec. cor., with brass cap mkd.
	
	from which
	<p>A fir, 54 ins. diam., bears S.22°E., 57 lks. dist., mkd. 1/4 S 19 B T</p> <p>A fir, 24 ins. diam., bears S.70°W., 46 lks. dist., mkd. 1/4 S 24 B T</p>
	Along broken E. slope
42.60	Desc. 110 ft. over broken NE. slope.