

County Surveyor's Record, Douglas County, Oregon

Retracement of S. Bdy., T. 24 S., R. 3 E.

CHAINS

- 79.90 Fall 62 lks. N. of cor. of secs. 34 and 35 only.
From the cor. of secs. 34 and 35 only
West, retracing S. bdy. of sec. 34
- 40.20 Fall 5 lks. N. of $\frac{1}{4}$ sec. cor. of sec. 34 only.
- 80.00 Fall 2 lks. N. of cor. of secs. 33 and 34 only
From the cor. of secs. 33 and 34 only
West, retracing S. bdy. of sec. 33
- 39.96 Fall 11 lks. S. of $\frac{1}{4}$ sec. cor. of sec. 33 only
- 80.06 Fall 30 lks. S. of cor. of secs. 32 and 33 only
From the cor. of secs. 32 and 33 only
West, retracing S. bdy. of sec. 32
- 40.25 Fall 7 lks. S. of $\frac{1}{4}$ sec. cor. of sec. 32 only.
- 80.19 Fall 20 lks. S. of cor. of secs. 31 and 32 only
From cor. of secs. 31 and 32 only
West, retracing S. bdy. of sec. 31
- 39.72 Fall 2 lks. N. of $\frac{1}{4}$ sec. cor. of sec. 31 only
- 75.15 Fall 26 lks. S. of the closing cor. of Tps. 24 and 25
S., R. 3 E.
- 23.70 Spur, slopes E., desc. 171 ft. over NE. slope.
- 31.40 Draw, drains E., asc. 124 ft. over SE. slope.
- 39.20 Spur, slopes E., "Little Dome Rock", a rock peak, 150
ft. high, about 4.00 chs. long, N. and S., and about
1.75 chs. wide, bears W. 1.00 ch. dist., desc. 54 ft.
over NE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 1 \quad | \quad S\ 6 \\ | \\ 1931 \end{array}$$

from which

A fir; 48 ins. diam., bears N.18°W., 63 lks.
dist., mkd. $\frac{1}{4}$ S 1 B T