

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of S. Bdy of T. 24 S., R. 3 E.

CHAINS

Thence, bet. secs. 2 and 35, continue line and measurement.

11.00 Asc. 357 ft. over face of steep bare rock, facing SE. Rocky spur, slopes SW., enter heavy timber and light undergrowth, bears N. and S., desc. 806 ft. over steep SW. slope.

24.00 Draw, drains SW., along S. slope.

28.50 Desc. 124 ft. over SW. changing to W. slope.

40.10 The $\frac{1}{4}$ sec. cor. of sec. 35 only, which is an iron post, 1 in. diam., 8 ins. above ground, firmly set. mkd. and witnessed as described in the official record.

Thence

S.89°38'W., on true line bet secs. 2 and 35

Desc. 78 ft. over W. slope, over bluff.

1.78 Mid point bet. closing cors. as hereinafter determined falls on face of bluff, impracticable to set cor.

Desc. 59 ft. over bluff, facing W.

2.30 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness $\frac{1}{4}$ sec. cor. of sec. 2 only with brass cap mkd.

W C
 $\frac{1}{4}$ S 2
1931

from which

A cedar, 24 ins. diam., bears S.50°E., 29 lks. dist., mkd. W C $\frac{1}{4}$ S 2 B T

A cedar, 16 ins. diam., bears S.66°W., 50 lks. dist. mkd. W C $\frac{1}{4}$ S 2 B T

Desc. 643 ft. over NW. slope, over bluffs.

17.80 Coal Creek, 20 lks. wide, course N., asc. 794 ft. over E., changing to SE. slope.

22.40 Way trail, bears N. and S.,

35.90 Ridge spur, bears N. and S., desc. 50 ft. over NW. slope.