

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of S. Bdy. of T. 24 S., R. 3 E.

CHAINS

- N.89°54'W., on true line bet. secs. 4 and 32
 Desc. 97 ft. over W. slope, through heavy timber
 and medium undergrowth.
- 1.94 Point for closing cor. of secs. 4 and 5, as
 hereinafter determined.
- Thence, bet. secs. 5 and 32, continue line and
 measurement.
- Desc. 236 ft. over SW. slope.
- 16.60 Creek, 4 lks. wide, course NW., over nearly level land
- 20.80 Creek, 1 lk. wide, course N.,
- 22.80 Creek, 4 lks. wide, course N., asc. 247 ft. over
 E. slope.
- 40.25 The $\frac{1}{4}$ sec. cor. of sec. 32 only, which is an iron
 post, 1 in. diam., firmly set in mound of stone,
 4 ft. base, 2 ft. high, mkd. and witnessed as
 described in the official record.
- Thence
- N.89°49'W., on true line bet. secs. 5 and 32
 Asc. 47 ft. over E. slope.
- 1.59 Mid point bet. closing cors., as hereinafter
 determined; set an iron post, 3 ft. long, 1 in. diam.
 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 5
 only, with brass cap mkd.
- $\frac{1}{4}$ S 5
 1931
- from which
- A fir, 22 ins. diam., bears S.63°E., 52 lks.
 dist., mkd. $\frac{1}{4}$ S 5 B T
- A fir, 10 ins. diam., bears S.21°W., 49 lks.
 dist., mkd. $\frac{1}{4}$ S 5 B T
- Asc. 39 ft. over E. slope.
- 3.90 Over nearly level bench
- 11.60 Asc. 178 ft. over E. slope.
- 39.94 The cor. of secs. 31 and 32 only, which is an iron post,