

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of S. Bdy. of T. 24 S., R. 3 E.

CHAINS

35.43 The closing cor. of Tps. 24 and 25 S., R. 3 E., which is an iron post, 3 ins. diam., 9 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

Land; mountainous.

Soil; rocky mountain loam, 3rd rate.

Timber; fir, hemlock, cedar, and pine.

Undergrowth; vinemaple, rhododendron, huckleberry, and hazel.

Retracement of Portion of E. Bdy. of T. 25 S., R. 2 E.

From the 1/4 sec. cor. of secs. 1 and 6, which is an iron post, 1 in. diam., 10 ins. above ground, firmly set, mkd. and witnessed in the official record.

North, retracing bet. secs. 1 and 6

40.00 Set temp. lot cor.

59.78 The cor. of Tps. 24 and 25 S., R. 2 E. only, bears W. 13 lks. dist.,

Resurvey of Portion of E. Bdy. of T. 25 S., R. 2 E.

From the 1/4 sec. cor. of secs. 1 and 6

N.0°07'W., on true line bet. secs. 1 and 6

Asc. 76 ft. over gradual SW. slope, through heavy timber and medium undergrowth.

14.60 Spur, slopes NW., desc. 131 ft. over NE. slope.

20.90 Spur, slopes NE., desc. 496 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, and in mound of stone, to top, for the cor. of lots 5 and 12, sec. 6, with brass cap mkd.

5  
12  
1931

From which