


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

40.50 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness $\frac{1}{4}$ sec. cor. of secs. 35 and 36, with brass cap mkd.



from which

A fir, 26 ins. diam., bears N.28°E., 58 lks. dist., mkd. W C $\frac{1}{4}$ S 36 B T

A fir, 26 ins. diam., bears N. 42°W., 41 lks. dist., mkd. W C $\frac{1}{4}$ S 35 B T

Along E. slope.

43.80 Creek, 2 lks. wide, course S.10°E., from NW., asc. 310 ft. over gradual broken S. slope.

46.50 Creek, 1 lk. wide, course SE.,


47.60 Way trail, bears NW. and SE.,

49.60 Spur, slopes E., enter meadow, bears E. and W., about 8.00 chs. wide.

61.10 Enter heavy timber and medium undergrowth, bears NW. and SE.

77.80 Spur, slopes SE., desc. 45 ft. over NE. slope

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.



from which

A fir, 24 ins. diam., bears N.77°E., 100 lks. dist., mkd. T 25 S R 3 E S 25 B T

A fir, 22 ins. diam., bears S.61°E., 95 lks. dist., mkd. T 25 S R 3 E S 36 B T

A fir, 16 ins. diam., bears S.59°W., 25 lks. dist., mkd. T 25 S R 3 E S 35 B T