

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

A fir, 30 ins. diam., bears N.51°W., 102 lks.
dist., mkd. T 25 S R 3 E S 26 B T

Land; mountainous.

Soil; rocky mountain loam, 3 rd rate.

Timber; fir, hemlock, pine, cedar, and yew.

Undergrowth; willow, alder, rhododendron, and vinemaple

East, on random line bet. secs. 25 and 36

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect the E. bdy. of Tp., 21 lks. S. of the cor.
of secs. 25, 30, 31, and 36

Thence

S.89°51'W., on true line bet. secs. 25 and 36

Desc. 28 ft. over NW. slope, through heavy timber
and medium undergrowth.

1.60 Creek, 4 lks. wide, course SW., along broken S. slope

16.50 Spur, slopes SW.,

21.80 Deer Creek, 5 lks. wide, course SE., asc. 358 ft. over
broken NE. slope, to $\frac{1}{4}$ sec. cor.

32.90 Spur, slopes SE.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{\frac{1}{4}}{S25} \\ \frac{S36}{1931}$$

from which

A fir, 8 ins. diam., bears N.15°E., 20 lks.

dist., mkd. $\frac{1}{4}$ S 25 B T

A fir, 14 ins. diam., bears S.32°E., 30 lks.

dist., mkd. $\frac{1}{4}$ S 36 B T

Asc. 500 ft. over broken NE. slope.

66.80 Spur, slopes N., desc. 106 ft. over NW. slope.

73.30 Draw, course NE., asc. 57 ft. over broken NE. slope.

80.00 The cor. of secs. 25, 26, 35, and 36

Land; mountainous.

Soil; rocky mountain loam, 3rd rate.