

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

Timber; fir, hemlock, pine, cedar, and yew.  
Undergrowth; rhododendron, willow, alder, vinemaple,  
and manzanita.

N.0°01'W., bet. secs. 25 and 26


Desc. 129 ft. over NE. slope, through heavy timber  
and dense undergrowth.

7.60 Creek, 2 lks. wide, course NE., asc. 170 ft. over  
broken SE. slope.

25.90 Draw, course E.,

33.00 Spur, slopes E., desc. 123 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A fir, 20 ins. diam., bears N.40°E., 56 lks.  
dist., mkd.  $\frac{1}{4}$  S 25 B T

A fir, 20 ins. diam., bears N.76°W., 106 lks.  
dist., mkd.  $\frac{1}{4}$  S 26 B T

Desc. 97 ft. over NE. slope.


45.60 Creek, 5 lks. wide, course E., asc. 732 ft. over  
broken SE. slope.

53.60 Creek,  $\frac{1}{2}$  lk. wide, course SE.,

68.53 Skipper Lakes Trail, bears NE. and SW.,

79.40 Spur, slopes E., desc. 4 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground, to bedrock, and in a mound of stone to  
the top, for the cor. of secs. 23, 24, 25, and 26,  
with brass cap mkd.



from which