

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

A fir, 24 ins. diam., bears N.69°E., 15 lks.

dist., mkd. T 25 S R 3 E S 24 B T

A fir, 14 ins. diam., bears S.28°E., 70 lks.

dist., mkd. T 25 S R 3 E S 25 B T

A fir, 26 ins. diam., bears S.14°W., 72 lks.

dist., mkd. T 25 S R 3 E S 26 B T

A fir, 18 ins. diam., bears N.43°W., 20 lks.

dist., mkd. T 25 S R 3 E S 23 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, hemlock, pine, cedar, and yew.

Undergrowth; alder, willow, mountain laurel,
huckleberry, and rhododendron.

N.89°51'E., on a random line bet. secs. 24 and 25

40.00 Set temp. $\frac{1}{4}$ sec. cor.80.08 Intersect E. bdy. of Tp., 10 lks. S. of the cor. of
secs. 19, 24, 25, and 30.

Thence

S.89°47'W., on true line bet. secs. 24 and 25

Asc. 234 ft. over SE. slope, through meadow.

4.40 Calapooya Trail, bears N.80°W., and S.80°E.,

14.60 Same trail, bears N.60°E. and S.60°W.,

16.30 Enter heavy timber and medium undergrowth.

19.80 Ridge spur, bears N.20°E., and S.20°W.,

20.10 Same trail, bears N. and S., desc. 278 ft. over SW.
slope.

33.00 Draw, course S., asc. 70 ft. over SE. slope.

38.40 Spur, slopes SW., desc. 41 ft. over SW. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S24}{S25}$$
 1931

from whi ch