

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

- A fir, 32 ins. diam., bears N.32°W., 71 lks.
dist., mkd. $\frac{1}{4}$ S 24 B T
- A fir, 18 ins. diam., bears S.33°W., 32 lks.
dist., mkd. $\frac{1}{4}$ S 25 B T
- Desc. 125 ft. over SW. slope.
- 43.70 Draw, course SE., asc. 36 ft. over NE. slope.
- 48.30 Spur, slopes SE., desc. 150 ft. over SW. slope.
- 56.60 Creek, 2 lks. wide, course S.10°E., asc. 110 ft. over
SE. slope.
- 63.90 Creek, 2 lks. wide, course SE., asc. 364 ft. over
E., changing to NE. slope.
- 70.40 Skipper Lakes Trail, bears N. and S.
- 80.08 The cor. of secs. 23, 24, 25 and 26
- Land; mountainous.
- Soil; rocky, 4th rate.
- Timber; fir, pine, hemlock, and cedar.
- Undergrowth; huckleberry, mountain laurel, willow,
alder, elderberry, and rhododendron.
-
- N.0°01'W., bet. secs. 23 and 24
- Desc. 65 ft. over NE. slope, through heavy timber
and medium undergrowth.
- 5.50 Draw, course E., across rolling top of Calapooya
Mountains.
- 26.30 Skipper Lakes Trail, bears E. and W.,
- 29.20 Divide bet. the North Umpqua and the Willamette rivers,
bears N.70°E. and S.70°W.,
- 29.40 Calapooya Trail, bears E. and W., desc. 317 ft. over
NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.