


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 38 ins. diam., bears S.79°E., 50 lks.
dist., mkd. $\frac{1}{4}$ S 24 B T

A fir, 36 ins. diam., bears S.49°W., 53 lks.
dist., mkd. $\frac{1}{4}$ S 23 B T

Desc. 236 ft. over NW. slope.

46.00 Creek, $\frac{1}{2}$ lk. wide, course NW.,

48.00 Creek, $\frac{1}{2}$ lk. wide, course NW., desc. 66 ft. along
W. slope.

49.90 Creek, 1 lk. wide, course W.,

51.80 Creek, $\frac{1}{2}$ lk. wide, course SW.,


53.80 Creek, 1 lk. wide, course W.,

67.70 Creek, $\frac{1}{2}$ lk. wide, course NW.,

68.40 Creek, 1 lk. wide, course W.,

71.80 Desc. 146 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for the cor. of secs. 13, 14, 23, and 24,
with brass cap mkd.



from which

A fir, 12 ins. diam., bears N.38°E., 27 lks.
dist., mkd. T 25 S R 3 E S 13 B T

A fir, 42 ins. diam., bears S.41°E., 26 lks.
dist., mkd. T 25 S R 3 E S 24 B T

A fir, 16 ins. diam., bears S.50°W., 102 lks.
dist., mkd. T 25 S R 3 E S 23 B T

A fir, 56 ins. diam., bears N.28°W., 107 lks.
dist., mkd. T 25 S R 3 E S 14 B T