

County Surveyor's Record, Douglas County, Oregon

.Subdivisions of T. 25 S., R. 3 E.

CHAINS

Asc. 813 ft. over E., changing to SE., slope.

38.80 Staley Trail, bears N.30°E. and S.30°W.,

40.00 Staley Ridge, bears N. and S.,

40.08 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S12
S13
1931

from which

A fir, 22 ins. diam., bears N.20°E., 46 lks.

dist., mkd. $\frac{1}{4}$ S 12 B T

A fir, 14 ins. diam., bears S.26°W., 18 lks.

dist., mkd. $\frac{1}{4}$ S 13 B T

Desc. 1376 ft. over broken NW. slope, to cor.

58.90 Creek, 1 lk. wide, course NW.,

75.20 Creek, 1 lk. wide, course N.80°W.,

80.16 The cor. of secs. 11, 12, 13, and 14.

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, pine, hemlock, cedar, and yew.

Undergrowth; vinemaple, alder, mountain laurel, and huckleberry.

N.0°01'W., bet. secs. 11 and 12

Desc. 366 ft. over broken NW. slope, to the $\frac{1}{4}$ sec. cor., through heavy timber and medium undergrowth.

1.10 Creek, 1 lk. wide, course W.,

11.80 Creek, 1 lk. wide, course W.,

28.40 Bluff, 80 ft. high, bears N.80°E. and S.80°W.,

29.70 Creek, 4 lks. wide, course W., water falls, 50 ft. high about 2.00 chs. E. of line.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top