

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

A fir, 22 ins. diam., bears N.65°W., 42 lks.
dist., mkd. W C T 25 S R 3 E S 1 B T

Land; rough mountainous.

Soil; rocky, 4th rate.

Timber; fir, yew, cedar, hemlock, and pine.

Undergrowth; vinemaple, rhododendron, mountain laurel, hazel, and huckleberry.

From true point for cor. of secs. 1, 2, 11, and 12
N.89°43'E., on a random line bet. secs. 1 and 12

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect the E. bdy. of Tp., 25 lks. N. of the cor.
of secs. 1, 6, 7, and 12.

Thence

S.89°54'W., on true line bet. secs. 1 and 12

Asc. 830 ft. over NE. slope, through heavy timber
and medium undergrowth

17.50 Draw, course N.80°E.,

28.20 Bluff, 40 ft. high, bears NW., and SE.,

29.40 Staley Ridge, bears N.25°W., and S.25°E., desc. 336 ft.
over W. slope.

31.70 Staley Trail, bears N.30°W. and S.30°E.,

40.02 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 1}{S 12}$$

1931

from which

A fir, 28 ins. diam., bears S.23°E., 109 lks.
dist., mkd. $\frac{1}{4}$ S 12 B T

A fir, 26 ins. diam., bears N.71°W., 21 lks.
dist., mkd. $\frac{1}{4}$ S 1 B T

Desc. 1253 ft. over broken SW. slope.

79.24 Intersect the witness cor. of secs. 1, 2, 11, and 12