

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

Thence

From the cor. of secs. 34 and 35 only, on the S.  
bdy. of Tp.


N.0°02'W., bet. secs. 34 and 35

Asc. 74 ft. over SW., slope, through heavy timber  
and medium undergrowth

4.20 Spur, slopes S.70°W., desc. 425 ft. over NW. slope.

19.60 Draw, course S.80°W., asc. 626 ft. over broken  
SE slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in  
the ground, to bedrock, and in a mound of stone to  
top, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A fir, 8 ins. diam., bears N.57°E., 93 lks.  
dist., mkd.  $\frac{1}{4}$  S 35 B T

A fir, 8 ins. diam., bears N.70°W., 29 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T

Asc. 885 ft. over broken SW., changing to S. slope.

43.40 Mountain Meadows Trail, bears NW. and SE.,


46.20 Enter meadows, bears E. and W.,

56.10 Spur, slopes SW., asc. along spur.

63.30 Asc. S. slope, through scattering timber.

78.80 Spur, slopes SW., desc. 12 ft. over NW. slope,  
through old burn, dense undergrowth.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins.  
in the ground, for the cor. of secs. 26, 27, 34 and 35,  
with brass cap mkd.



from which

A fir, 34 ins. diam., bears N.62°E., 265 lks.