

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

dist., mkd. $\frac{1}{4}$ S.35 B T

Asc. 958 ft. over E. slope.

46.20 Top of bluff, 45 ft. high, bears NW. and SE.,

59.40 Top of bluff, 50 ft. high, Bears N. and S.,

64.50 Spur, slopes SE.,

67.40 Balm Mountain Ridge, bears N. and S., a Geological Survey bench mark, which is a brass tablet, set in solid rock, mkd. 6,083 ft. elevation, bears south, 50 lks. dist., Forest Service telephone line, bears N. and S., desc. 100 ft. over SW. slope.

76.00 Spur, slopes SW., desc. 27 ft. over NW. slope.

79.94 The cor. of secs. 26, 27, 34, and 35.

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, hemlock, pine, cedar, and yew.

Undergrowth; young fir, and hemlock, willow, alder, elderberry, rhododendron, manzanita, and huckleberry.

N.0°02'W., bet. secs. 26 and 27

Desc. 168 ft. along broken W. slope, through old burn, scattered timber and dense undergrowth.


6.10 Enter heavy timber and medium undergrowth, leave old burn, bears E. and W.,

35.90 Desc. 184 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor., falls on precipitous slope impracticable to set cor.

Desc. 105 ft. over N. slope.

42.30 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone, to top for the witness $\frac{1}{4}$ sec. cor. of secs. 26 and 27, with brass cap mkd.



from which