

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS									
	N.0°02'W., bet. secs. 22 and 23 along gradual W. slope, through heavy timber and medium undergrowth								
2.30	Creek, 1 lk. wide, course SW.,								
2.80	Mountain Meadows Trail, bears NE. and SW.,								
10.00	Spur, slopes W., desc. 50 ft. over gradual NW. slope.								
16.00	Creek, 1 lk. wide, course W., asc. 129 ft. over gradual SW. slope, to the $\frac{1}{4}$ sec. cor.								
24.90	Creek, 1 lk. wide, course S.30°W.,								
28.70	Same trail, bears E. and W.,								
40.00	A fir, 20 ins. diam., for the $\frac{1}{4}$ sec. cor., mkd. S 23 on E., and $\frac{1}{4}$ S 22 on W. side  from which A fir, 24 ins. diam., bears S.79°E., 32 lks. dist., mkd. $\frac{1}{4}$ S 23 B T A fir, 14 ins. diam., bears N.85°W., 64 lks. dist., mkd. $\frac{1}{4}$ S 22 B T Asc. 414 ft. over gradual SW. slope, to cor.								
41.80	Calapooya Trail, and Forest Service telephone line bears E. and W.,								
49.90	Spur, slopes W.,								
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 14, 15, 22, and 23, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T25S</td> <td>R3E</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1931</td> </tr> </table>	T25S	R3E	S15	S14	S22	S23	1931	
T25S	R3E								
S15	S14								
S22	S23								
1931									
	from which								
	A fir, 6 ins. diam., bears N.60°E., 46 lks. dist., mkd. T 25 S R 3 E S 14 B T								
	A fir, 26 ins. diam., bears S.42°E., 31 lks. dist., mkd. T 25 S R 3 E S 23 B T								
	A fir, 20 ins. diam., bears S.63°W., 79 lks.								