

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

dist., mkd. T 25 S R 3 E S 22 B T

A fir, 16 ins. diam., bears N.69°W., 172 lks.

dist., mkd. T 25 S R 3 E S 15 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, pine, hemlock, and cedar.

Undergrowth; huckleberry, manzanita, alder, and elderberry.

N.89°59'E., on a random line bet. secs. 14 and 23

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.82 Intersect N. and S. line, 21 lks. S. of cor. of secs. 13, 14, 23, and 24.

Thence

S.89°50'W., on true line bet. secs. 14 and 23

Desc. 133 ft. over NW. slope, through heavy timber and medium undergrowth.

4.60 Creek, 4 lks. wide, course N.10°W., asc. 125 ft. over NE. slope.

14.60 Spur, slopes N., desc. 92 ft. over NW. slope.

25.40 Way trail, bears NW. and SE.,

27.80 Coal creek, 5 lks. wide, course N., asc. 240 ft. over NE. slope.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S14  
 S23  
 1931

from which

A fir, 36 ins. diam., bears S.15°W., 44 lks.

dist., mkd.  $\frac{1}{4}$  S 23 B T

A fir, 20 ins. diam., bears N.7°W., 62 lks.

dist., mkd.  $\frac{1}{4}$  S 14 B T

Asc. 1030 ft. over broken E. slope.

77.20 Head of gulch, course S.75°E.,