

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS	
	timber and medium undergrowth.
16.00	Creek, 1 lk. wide, course N.75°W.,
22.30	Coal Creek, 10 lks. wide, course N., asc. 518 ft. over NE., changing to E., slope.
26.10	Way trail, bears NE. and SW.,
40.10	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec.cor., with brass cap mkd.
	$\frac{\frac{1}{4} \text{ S11}}{\text{S14}}$ 1931
	from which
	A hemlock, 13 ins. diam., bears N.74°E., 65 lks. dist., mkd. $\frac{1}{4}$ S 11 B T
	A fir, 38 ins. diam., bears S.36°E., 83 lks. dist., mkd. $\frac{1}{4}$ S 14 B T
	Asc. 859 ft. over broken E. slope, to cor.
65.40	Spur, slopes SE.,
71.70	Draw, course S.65°E.,
80.20	The cor. of secs. 10, 11, 14, and 15
	Land; mountainous.
	Soil; rocky, 4th rate.
	Timber; fir, cedar, hemlock, pine, and yew.
	Undergrowth; vinemaple, alder, elderberry, huckleberry and rhododendron.
	N.0°02'W., bet. secs. 10 and 11
	Asc. 50 ft. over broken E. slope, through heavy timber and medium undergrowth
2.10	Draw, course E.,
9.90	Ridge, spur, bears NE. and SW., desc. 99 ft. over broken W. slope.
20.90	Draw, course W., asc. 106 ft. over SW. slope.
26.00	Draw, course W.,
32.70	Spur, slopes W., desc. 91 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.