

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 25 S., R 3 E.

## CHAINS

Thence

N.89°43'W., on true line bet. secs. 2 and 11

Desc. 610 ft. over broken W. slope, through heavy  
timber and medium undergrowth

5.40 Top of rock, 278x98x100 ft. above ground.

8.50 Creek, 2 lks. wide, course NW.,

19.40 Coal Creek, 10 lks. wide, course N., asc. 614 ft.  
over broken NE. slope.

31.30 Way trail, bears N.10°E. and S.10°W.

40.06 Set an iron post, 3 ft. long, 1 in diam., 28 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \\ 1931 \end{array}$$

from which

A fir, 24 ins. diam., bears S.2°E., 48 lks.

dist., mkd.  $\frac{1}{4}$  S 11 B T

A hemlock, 8 ins. diam., bears N.45°W., 44 lks.

dist., mkd.  $\frac{1}{4}$  S 2 B T

Asc. 636 ft. over broken SE. slope.

58.30 Draw, course S.60°E.,

65.00 Creek 2 lks. wide, course SE.,

72.50 Spur, slopes N.10°E., desc. 119 ft. along steep NW.  
slope.

80.12 The cor. of secs. 2, 3, 10, and 11

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, hemlock, cedar, yew, and pine.

Undergrowth; vinemaple, rhododendron, manzanita,  
huckleberry, and chinquapin

N.0°02'W., on true line bet. secs. 2 and 3

Desc. 777 ft. over broken NW. slope, through heavy  
timber and dense undergrowth

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in