


Subdivisions of T. 25 S., R. 3 E.

CHAINS

the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 16 ins. diam., bears N.45°E., 27 lks.
dist., mkd. $\frac{1}{4}$ S 2 B T

A hemlock, 18 ins. diam., bears N.78°W., 55 lks.
dist., mkd. $\frac{1}{4}$ S 3 B T


Desc. 757 ft. over broken NW. slope.

58.50 Creek, 1 lk. wide, course N.25°W.,

65.30 Deadwood Creek, 7 lks. wide, course N.30°E., asc. 165
ft. over SE. slope to cor.

75.10 Draw, course SE.,

80.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the cor. of lots 5 and 12, sec. 2,
and lots 8 and 9, sec. 3, with brass cap mkd.



from which

A fir, 36 ins. diam., bears S.80°E., 74 lks.
dist., mkd. S 2 L 12 B T


A fir, 32 ins. diam., bears S.35°W., 74 lks.
dist., mkd. S 3 L 9 B T

Asc. 447 ft. over broken SE. slope.

101.70 Spur, slopes E., desc. 88 ft. over NE. slope.

104.37 Intersect S. bdy. of T. 24 S., R. 3 E.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for closing cor. of secs. 2 and 3, with
brass cap mkd.



from which