

## County Surveyor's Record, Douglas County, Oregon


Subdivisions of T. 25 S., R. 3 E.

CHAINS

Thence, N.0°02'W., 9.00 chs., asc. 300 ft. over rocky S. slope; at 5.00 chs. saddle in spur, projects N.75°W., Sliver Rock, bears W., 4.00 chs. dist., to E. end; average width on top, about 10 ft., length on top, about 3.50 chs., height above spur, on E. end, about 120 ft., on W. end, about 350 ft. Desc. 170 ft. over N. slope, over bluff

Thence, West, 4.70 chs. along N. slope, to sec. line

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A fir, 48 ins. diam., bears N.27°E., 33 lks. dist., mkd.  $\frac{1}{4}$  S 27 B T

A fir, 48 ins. diam., bears N.37°W., 18 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T

Desc. 403 ft. over N. slope.

47.30 Draw, course W., asc. 334 ft. over SW. slope.

55.20 Rocky spur, slopes W., desc. 670 ft. over broken NW. slope

76.50 Creek, 6 lks. wide, course S.80°W., junction of creeks from N., and SE., 10 lks. E. of line, asc. 65 ft. over NE. slope.

80.00 A fir, 16 ins. diam., for the cor. of secs. 21, 22, 27, and 28, mkd.

T 25 S S 22 on NE.,

R 3 E S 27 on SE.,

S 28 on SW., and

S 21 on NW., side

from which