

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS	
	<p>A fir, 14 ins. diam., bears N.27°E., 41 lks. dist., mkd. T 25 S R 3 E S 22 B T</p> <p>A fir, 24 ins. diam., bears S.67°E., 89 lks. dist., mkd. T 25 S R 3 E S 27 B T</p> <p>A fir, 14 ins. diam., bears S.35°W., 29 lks. dist., mkd. T 25 S R 3 E S 28 B T</p> <p>A fir, 10 ins. diam., bears N.43°W., 28 lks. dist., mkd. T 25 S R 3 E S 21 B T</p> <p>Land; mountainous.</p> <p>Soil; rocky, 4th rate.</p> <p>Timber; fir, cedar, pine, hemlock, and Oregon maple.</p> <p>Undergrowth; vinemaple, rhododendron, huckleberry, mountain laurel, buckbrush, and manzanita.</p>
	<p>S.89°54'E., on a random line bet. secs. 22 and 27</p>
40.00	Set temp. 1/4 sec. cor.
79.82	Intersect N. and S. line, 25 lks. N. of cor. of secs. 22, 23, 26, and 27
	Thence
	N.89°43'W., on true line bet. secs. 22 and 27
	Desc. 719 ft. over broken W. slope, to 1/4 sec. cor., through heavy timber and medium undergrowth.
1.40	Mountain Meadow Trail, bears N. 10°E., and S.10°W.
4.80	Creek, 3 lks. wide, course W., from N.75°E., along creek,
10.10	Leave creek, course N.75°W.,
25.60	Same creek, 3 lks. wide, course S.60°W.,
36.60	Rocky spur, slopes S.,
39.91	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S22}{S27}$ 1931
	from which