

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

A fir, 30 ins. diam., bears S.74°W., 68 lks.
dist., mkd. $\frac{1}{4}$ S 21 B T

Along W. slope.

42.40 Creek, 3 lks. wide, course S.75°W., asc. 348 ft. over
broken SW. slope.

48.00 Draw, course S.75°W.,

68.60 Spur, slopes W., desc. 119 ft. over NW. slope

72.60 Creek, 2 lks. wide, course W., asc. 182 ft. over SW.
slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground for the cor. of secs. 15, 16, 21, and 22,
with brass cap mkd.

T25S	R3E
S16	S15
S21	S22

1931

from which

A fir, 36 ins. diam., bears N.48°E., 88 lks.
dist., mkd. T 25 S. R 3 E S 15 B T

A fir, 52 ins. diam., bears S.82°E., 78 lks.
dist., mkd. T 25 S R 3 E S 22 B T

A fir, 34 ins. diam., bears S.31°W., 131 lks.
dist., mkd. T 25 S R 3 E S 21 B T

A fir, 20 ins. diam., bears N.80°W., 42 lks.
dist., mkd. T 25 S R 3 E S 16 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, cedar, pine, hemlock, and madrona.

Undergrowth; mountain laural, rhododendron, hazel,
vinemapple, and chinquapin.

S.89°43'E., on a random line bet. secs. 15 and 22

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.76 Intersect N. and S. line, 7 lks. N. of the cor. of secs.
14, 15, 22, and 23.