

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.


CHAINS

E. and W.,

29.50 Calapooya Mountains, divide bet. the North Umpqua and the Willamette rivers, bears E. and W., desc. 57 ft. over NW. slope.

35.40 Spur, slopes NW., desc. 149 ft. over N., changing to NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 34 ins. diam., bears N.47°E., 71 lks. dist., mkd. $\frac{1}{4}$ S 15 B T

A hemlock, 16 ins. diam., bears S.80°W., 52 lks. dist., mkd. $\frac{1}{4}$ S 16 B T


Desc. 120 ft. over NE. slope.

46.70 Small stream, course NW., desc. 67 ft. over NW. slope.

50.70 Creek, 2 lks. wide, course N.75°W., desc. 421 ft. over N. slope.

63.70 Same creek, 3 lks. wide, course N.25°E., desc. 181 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for, the cor. of secs. 9, 10, 15, and 16, with brass cap mkd.



from which

A fir, 22 ins. diam., bears N.39°E., 54 lks. dist., mkd. T 25 S R 3 E S 10 B T

A fir, 22 ins. diam., bears S.49°E., 112 lks. dist., mkd. T 25 S R 3 E S 15 B T

A hemlock, 40 ins. diam., bears S.20°W., 77 lks. dist., mkd. T 25 S R 3 E S 16 B T