

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

asc. 403 ft. over broken SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 28, 29, 32, and 33, with brass cap mkd.

T25SR3E	
S29	S28
<hr/>	
S32	S33
1931	

from which

A fir, 9 ins. diam., bears N.41°E., 19 lks.

dist., mkd. T 25 S R 3 E S 28 B T

A fir, 32 ins. diam., bears S.41°E., 37 lks.

dist., mkd. T 25 S R 3 E S 33 B T

A fir, 8 ins. diam., bears S.49°W., 53 lks.

dist., mkd. T 25 S R 3 E S 32 B T

A fir, 6 ins. diam., bears N.22°W., 23 lks.

dist., mkd. T 25 S R 3 E S 29 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, pine, hemlock, cedar, madrona, and yew.

Undergrowth; vinemaple, rhododendron, huckleberry, buckbrush, dogwood, manzanita, and chinquapin.

East on a random line bet. secs. 28 and 33

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.76 Intersect N. and S. line, 24 lks. N. of the cor. of secs. 27, 28, 33, and 34

Thence

N.89°50'W., on true line bet. secs. 28 and 33

Desc. 748 ft. over broken W., changing to NW. slope, through heavy timber and medium undergrowth.

39.88 True point for the $\frac{1}{4}$ sec. cor. falls in small stream, course N.65°W., asc. 3 ft. along N. slope.40.88 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor. for secs. 28