

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS	
	N.0°03'W., bet. secs. 8 and 9 Asc. 72 ft. over rolling gradual SE. slope, through heavy timber and medium undergrowth
10.10	Spur, slopes SE., desc. 89 ft. over rocky gradual NE. slope.
15.90	Creek, 1 lk. wide, course S.75°E., ascend 64 ft. over gradual SE. slope.
32.00	Spur, slopes E., along gradual E. slope.
33.50	Bristow Trail, and Forest Service telephone line, bears N.70°W., and S.70°E.
36.00	Enter willow thicket, bears SE. and NW.
40.00	Set a basalt stone, 8x14x28 ins., 20 ins. in the ground, for the $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face from which A fir, 33 ins. diam., bears N.79°E., 213 lks. dist., mkd. $\frac{1}{4}$ S 9 B T A fir, 38 ins. diam., bears S.46°W., 263 lks. dist., mkd. $\frac{1}{4}$ S 8 B T Note: As the swampy nature of the ground on which the point for the above described cor. fell rendered the setting of the regulation iron post impracticable, the District Cadastral Engineer authorized the use of native material. Along gradual E. slope.
41.60	Creek, 1 lk. wide, course SE.,
42.80	Enter heavy timber and medium undergrowth, bears SE. and W., asc. 133 ft. over S. slope.
49.90	Calapooya Mountains, divide bet. the North Umpqua and the Willamette rivers, bears S.75°W., and N.75°E., desc. 114 ft. over N. slope.
55.20	Enter meadow, bears NW. and SE., desc. 18 ft. over gradual NW. slope.
59.40	Enter heavy timber and medium undergrowth, bears NW. and SE.