


Subdivisions of T. 25 S., R. 3 E.

CHAINS

- 24.40 Enter alder thicket, leave timber, bears E. and W.
- 33.70 Enter heavy timber and medium undergrowth, bears
NE. and SW., spring, course E.,
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

- A fir, 34 ins. diam., bears S.82°E., 54 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T
- A fir, 32 ins. diam., bears N.60°W., 52 lks.
dist., mkd. $\frac{1}{4}$ S 5 B T

Along broken gradual E. slope.

- 58.90 Desc. 243 ft. over gradual NE. slope.
- 80.00 A fir, 19 ins. diam., for the cor. of lots 5 and 12,
sec. 4, and lots 8 and 9, sec. 5, mkd.
S 4 L 5 on NE.,
L 12 on SE.,
S 5 L 9 on SW., and
L 8 on NW., side

from which

- A fir, 50 ins. diam., bears S.57°E., 35 lks.
dist., mkd. S 4 L 12 B T
- A fir, 16 ins. diam., bears N.26°W., 63 lks.
dist., mkd. S 5 L 8 B T

Desc. 140 ft. over broken NE. slope.

- 87.30 Creek, 6 lks. wide, course N.60°W., asc. 236 ft.
over broken SW. slope.
- 95.40 Draw, course N.60°W.,
- 104.73 Intersect S. bdy., of T. 24 S., R. 3 E.
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for the closing cor. of secs. 4 and 5,
with brass cap mkd.