

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

T25S	R3E
S19	S20
S30	S29
1931	

from which

A fir, 50 ins. diam., bears N.28°E., 118 lks. dist., mkd. T 25 S R 3 E S 20 B T

A cedar, 7 ins. diam., bears S.71°E., 21 lks. dist., mkd. T 25 S R 3 E S 29 B T

A cedar, 10 ins. diam., bears S.39°W., 96 lks. dist., mkd. T 25 S R 3 E S 30 B T

A fir, 18 ins. diam., bears N.24°W., 41 lks. dist., mkd. T 25 S R 3 E S 19 B T

Land; mountainous.

Soil; rocky, 4th rate

Timber; fir, hemlock, cedar, pine, madrona, and yew.

Undergrowth; huckleberry, vinemaple, mountain laurel, rhododendron, dogwood, manzanita, chinquapin, and buckbrush.

- 40.00 N.89°53'E., on a random line bet. secs. 20 and 29 Set temp. ¼ sec. cor.
- 80.20 Intersect N. and S. line, 30 lks. N. of the cor. of secs. 20, 21, 28, and 29.  
Thence  
N.89°54'W., on true line bet. secs. 20 and 29  
Asc. 158 ft. over SE., changing to E. slope, through heavy timber and dense undergrowth.
- 6.50 Spur, slopes S., desc. 143 ft. over SW. slope.
- 16.70 Draw, course S., asc. 322 ft. over SE., changing to E. slope.
- 31.10 Ridge spur, bears N. and S., way trail along top, desc. 287 ft. over NW. changing to W. slope.
- 40.10 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.