


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS

- 20.90 Spur, slopes SW., desc. 43 ft. over NW. slope
- 22.60 Creek, 2 lks. wide, course S.30°W., asc. 394 ft. over SE. slope.
- 34.50 Spur, slopes SW., along W. slope.
- 38.10 Asc. 34 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 24 ins. diam., bears N.78°E., 72 lks. dist., mkd. $\frac{1}{4}$ S 20 B T

A fir, 34 ins. diam., bears S.53°W., 51 lks. dist., mkd. $\frac{1}{4}$ S 19 B T

Asc. 40 ft. over SW. slope.


- 41.70 Draw, course S.15°W., asc. 477 ft. over SE. slope.

- 54.20 Spur, slopes S.15°W., asc. 350 ft. over broken SW. slope, to cor.

- 60.00 Draw, course W.,

- 77.00 Spur, slopes S.60°W.,

- 80.00 Set an ironpost, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 17, 18, 19, and 20, with brass cap mkd.



from which

A fir, 24 ins. diam., bears N.43°E., 23 lks. dist., mkd. T 25 S R 3 E S 17 B T

A fir, 18 ins. diam., bears S.35°E., 12 lks. dist., mkd. T 25 S R 3 E S 20 B T

A fir, 18 ins. diam., bears S.63°W., 101 lks. dist., mkd. T 25 S R 3 E S 19 B T