

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS	
	S.89°45'W., on true line bet. secs. 5 and 8
	Desc. 300 ft. over gradual NW. slope, through scattered timber and medium undergrowth.
3.90	Draw, course NW.,
14.80	Creek, 1 lk. wide, course N.15°E., asc. 500 ft. over NE. slope.
32.00	Asc. 285 ft. over steep rocky E. slope.
39.95	True point for $\frac{1}{4}$ sec. cor., falls on steep sloping bare rock, impracticable to set cor.,
41.00	Foot of bluff, 300 ft. high, facing NE.,
41.70	Top of bluff, "Bulldog Rock," bears S.10°E. and N.10°W., about 2.50 chs. to point.
41.74	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} W C \\ \frac{1}{4} \overline{S 5} \\ S 8 \\ 1931 \end{array}$
	from which
	A fir, 22 ins. diam., bears S.64°W., 223 lks. dist., mkd. W C $\frac{1}{4}$ S 8 B T
	A fir, 6 ins. diam., bears N.22°W., 18 lks. dist., mkd. W C $\frac{1}{4}$ S 5 B T
	A Geological Survey bench mark, which is a brass cap, set in solid rock, on the point of Bulldog Rock, bears N.12°W., 169 lks. dist., mkd "above sea 5836 ft."
	Along S. slope, through medium timber and undergrowth.
44.50	Bulldog Ridge, bears NE. and SW., desc. 335 ft. over steep NW. slope.
59.20	Draw, course N., asc. 102 ft. over NE. slope.
63.50	Spur, slopes N.30°W., desc. 70 ft. over NW. slope.
68.80	Draw, course N., asc. 146 along NE. slope