

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 3 E.

CHAINS	buckbrush, cascara, and mountain laurel
	N.0°04'W., on true line bet. secs. 5 and 6 Desc. 110 ft. over NE., changing to E. slope, through heavy timber and light undergrowth
9.80	Head of draw, course E., asc. 248 ft. over SE. slope.
25.30	Ridge, bears N.15°E., and S.15°W., asc. 41 ft. along W. slope.
38.30	Same ridge, bears NW. and SE., desc. 83 ft. over steep NE. slope.
40.00	The true point for the ¼ sec. cor., falls on precipitous ground, impracticable to set cor. Desc. 110 ft. over steep NE. slope.
42.40	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness ¼ sec. cor., with brass cap mkd.
	W C ↑ S 6 S 5 1931
	from which
	A fir, 26 ins. diam., bears N.58°E., 23 lks. dist., mkd. W C ¼ S 5 B T
	A fir, 16 ins. diam., bears S.80°W., 11 lk. dist., mkd. W C ¼ S 6 B T
	Desc. 851 ft. over broken NE. slope.
56.60	Top of bluff, 35 ft. high, bears NW. and SE.
72.60	Creek, 1 lk. wide, course E., along broken E. slope.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the cor. of lots 8 and 9, sec. 6, and lots 5 and 12, sec. 5, with brass cap mkd.
	8 5 S6 — — S5 9 12 1931
	from which
	A fir, 24 ins. diam., bears N.51°E., 71 lks.