

County Surveyor's Record, Douglas County, Oregon

South Boundary of Tp.24 S., R. 5 E.,
as Surveyed by Henry C. Perkins, Deputy
Surveyor, under Contract No.751, dated,
July 25, 1902.

CHAINS

I commence at the corner of Tps. 24 and 25 S R 5 E
Latitude 43°25' N Longitude 122°09'W.

Run West on Random Line, on S bdy of Tp. 24 S., R. 5 E
setting temporary $\frac{1}{4}$ sec. and sec. cors. at intervals of
40.00 chains, and at 482.50 chains intersect Range
line, 3.90 chs. S of cor. of Tps. 24 and 25 S Rs 4 and
5 E

Not falling within the prescribed limits I destroy all
marks at the cor. of Tp. 24 and 25 S Rs. 4 and 5 E
and proceed to establish a closing cor. at intersection
just made, by setting a Basalt stone, 18x18x18 ins.
12 ins. in the ground, marked C C on E with 6 grooves
on N S and E faces, from which,

A Larch, 36 ins. diam., bears N.26°E., 48 lks.
dist. marked T 24 S R 5 E S 31 B T.

A Larch, 36 ins. diam., bears S.75°E., 13 lks.
dist. marked T 25 S R 5 E S 6 B T.

Thence I run

East on S bdy. of Tp. bet. secs. 6 and 31, over
mountainous land, heavily timbered and covered with
dense undergrowth.

Descending an E slope.

25.00 Brook 3 lks. wide, course NE
Foot of, descent ascend steep N. slope of bluff.

39.00 Summit of bluff bears N and S

Descending steeply

42.50 Set a Basalt stone, 30x20x12 ins. 20 ins. in the ground,
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face, from which;

A Hemlock, 5 ins. diam., bears N.58°W., 9 lks.
dist. marked $\frac{1}{4}$ S 31 B T.

A Hemlock, 7 ins. diam., bears S.10°W., 21 lks.
dist. marked $\frac{1}{4}$ S 6 B T.