

South Boundary of T 24 S. R. 5 $\frac{1}{2}$ E.

CHAINS 40.00	Summit of ascent descend.
79.50	West bank of lake, A pine, 16 ins. in dia., for Witness cor of secs. 2 and 35, marked W C T 24 S S 36 on NE. R 5 $\frac{1}{2}$ E S 1 on SE. T 25 S S 2 on SW. and S 35 on NW. face, with 1 notch on E. and 5 on W. edges from which, A hemlock, 15 ins. in dia., bears N.45*E. 40 lks. dist., marked W C T 24 S R 5 $\frac{1}{2}$ E S 35 B T. A hemlock, 18 ins. in dia., bears S.18*E. 45 lks. dist., marked W C T 25 S R 5 $\frac{1}{2}$ E S 2 B T. To pass the lake I offset as follows: North 2.00 chains. East 3.30 chains. South 2.00 chains to
2.80	East bank of lake. Set a hemlock post, 3 ft. long, 4 ins. sq. 2 ft. in ground, for Witness cor. of secs. 1 and 36, marked W C T 24 S S 36 on NE. R 5 $\frac{1}{2}$ E S 1 on S E. T 25 S S 2 on SW. and S 35 on NW. face, with 1 notch on E and 5 on W edges, from which, A pine, 14 ins, in dia., bears N.35*E. 16 lks. dist., marked T 24 S R 5 $\frac{1}{2}$ E S 36 B T. A pine, 12 ins. in dia., bears S.85*E. 20 lks. dist., marked T 24 S R 5 $\frac{1}{2}$ E S 1 B T.
40.00	Rock in place, 24x24x24 ins. above ground, for $\frac{1}{4}$ sec. cor. marked with X at the exact cor. point, from which, A hemlock, 14 ins. in dia., bears N.85*E. 29 lks. dist., marked $\frac{1}{4}$ S 36 B T. A hemlock, 18 ins. in dia., bears S.10*E. 12 lks. dist., marked $\frac{1}{4}$ S 1 B T. Ascending steep W. slope of mountain.
51.00	Summit of slope bears N. and S. Descend steep E. side of slope.
80.00	The cor. of Tp. 24 and 25 S Rgs. 5 $\frac{1}{2}$ and 6 E.