CHAINS	
	Thence
	S.89*56'W. on true line on S. bdy. of Sec. 33.
0.225	Point for the ¼ sec. cor. of sec. 34 only, Tp. 25½ S., R. 2 E., later determined.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 34 only with brass cap marked
	¼ S34 1930
	from which
	A Fir, 6 ins. diam., bears S.68*E., 32 lks. dist., marked ¼ S 34 B T.
	A Fir, 16 ins. diam., bears S.23*W., 11 lks. dist., marked ¼ S 34 B T.
39.80	The ¼ sec. cor. of sec. 33 only, which is an iron post, 1 in. diam., 8 ins. above ground, marked and witnessed as described in the field notes of Tp. 25 S., R. 2 E., this Group.
	Thence
	S.89*52'W., on true line, continuing measurement
40.25	Point for closing cor. of secs. 33 and 34, Tp. 25½ S., R. 2 E., later determined and hereinafter described.
79.92	Cor. of secs. 32 and 33 only, which is an irom post, 2 ins. diam., 10 ins. above ground, marked and witnessed as described in the field notes of Tp. 25 S., R. 2 E., this Group.
	West on true line on S., bdy. of sec. 32.
0.24	Point for ¼ sec. cor. of sec. 33 only, Tp. 25½ S., R. 2 E., later determined.
	Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap marked
	¼ S33 1930