

County Surveyor's Record, Douglas County, Oregon

Resurvey of South Bdy. of Tp. 25 S., R. 2 E.

CHAINS	S.89*55'W., on true line, continuing measurement.
40.10	Point for closing cor. of secs. 31 and 32, Tp. 25 $\frac{1}{2}$ S., R. 2 E., later determined and hereinafter described.
59.76	Cor. of Tps. 25 S., Rs. 1 and 2 E., which is A Fir, 7 ins. diam., marked and witnessed as described in the field notes of Tp. 25 S., R. 1 E., this Group.
Retracement of South Bdy. of Tp. 25 S., R. 1 E.	
From the cor. of Tps. 25 S., Rs. 1 and 2 E. West retracing S. bdy. of Sec. 36.	
39.83	Fall 7 lks. N. of $\frac{1}{4}$ sec. cor. of sec. 36 only.
Resurvey of South Bdy. of Tp. 25 S., R. 1 E.	
From the cor. of Tps. 25 S., Rs. 1 and 2 E., hereinbefore described,	
S.89*54'W., on true line on S. bdy. of sec. 36.	
20.34	At 40.00 chs. westing from the closing cor. of secs. 31 and 32, Tp. 25 $\frac{1}{2}$ S., R. 2 E., later determined.
A Fir, 30 ins. diam., for $\frac{1}{4}$ sec. cor. of sec. 31 only, T.25 $\frac{1}{2}$ S., R. 2 E. I mark $\frac{1}{4}$ S 31 on S. side from which A Fir, 44 ins. diam., bears S.20*E., 28 lks. dist., marked $\frac{1}{4}$ S 31 B T. A Fir, 60 ins. diam., bears S.50*W., 29 lks. dist., marked $\frac{1}{4}$ S 31 B T.	
39.83	The $\frac{1}{4}$ sec. cor. of sec. 36 only, which is an iron post, 1 in. diam., 9 ins. above ground, marked and witnessed as described in the field notes of T. 25 S., R. 1 E., this Group.
The latitude and longitude at the SE. cor. of this township is 43*21'N. and 122*30'W. respectively.	