

County Surveyor's Record, Douglas County, Oregon

Dependant Resurvey of the Willamette Meridian
through T. 26 S.

CHAINS

From the cor. of Tps. 26 and 27 S., R. 1 W. only, as described in the notes of T. 27 S., R. 1 E. N.0*27'E., resurveying the E. bdy. of sec. 36. Descend 128 ft. over broken NW. slope, through timber and brush.

4.63 The closing Tp. cor. of Tps. 26 and 27 S., R. 1 E., as described in the notes of T. 27 S., R. 1 E.

31.00 Ravine, course NW.

35.20 Draw, course SW.

Ascend 20 ft. over S. slope.

38.80 Small spur, slopes SW.

39.83 Intersect the old $\frac{1}{4}$ sec. cor., established for secs. 31 and 36, which is a conglomerate stone 16x12x9 ins. above ground, marked $\frac{1}{4}$ on the W. face.

I change this cor. to refer to sec. 36 only, obliterating the scribe marks on the SE. bearing tree.

Alongside of old cor. stone,

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked,

$\frac{1}{4}$ S36 |
1928

from which

A fir, 33 ins. diam., bears S.39*E., 8 lks. dist.

Marked $\frac{1}{4}$ S 31 B T (old bearing tree.)

A fir, 14 ins. diam., bears S.64*W., 19 lks. dist.

Marked $\frac{1}{4}$ S 36 B T (old bearing tree.)

A fir, 10 ins. diam., bears N.20*W., 19 lks. dist.

Marked $\frac{1}{4}$ S 36 B T.

Thence,

N.0*21'E.

Over rolling broken land.

4.94 Point for the $\frac{1}{4}$ sec. cor. of sec. 31 later determined.