

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian  
through T. 26 S.

CHAINS

A fir, 24 ins. diam., bears N.53\*W., 14 lks. dist.

Marked T 26 S R 1 W S 25 B T (old B. T.)

Land, rolling and mountainous.

Soil, loam and stony, 3rd rate.

Timber, fir, hemlock and yew.

Undergrowth, rhododendron, yew, hemlock and vine maple.

N.0\*23'E., resurveying the E. bdy. of sec. 25.

Over mountainous land, through timber and brush.

5.10 Point for the closing cor. of secs. 30 and 31, later  
determined and hereinafter described.

Descend 288 ft. over broken N. slope.

12.90 Spring branch, 1 lk. wide, course NW.

27.40 Cougar Creek, 8 lks. wide, course N.10\*E.

34.10 Cougar Creek, 8 lks. wide, course N. descend creek.

37.40 Cougar Creek, 8 lks. wide, course N.25\*W.

38.84 Intersect the  $\frac{1}{4}$  sec. cor., established for secs. 25 and  
30, which is a basalt stone, 14x8x4 ins. above  
ground, marked  $\frac{1}{4}$  on W. face,

I change this cor. to refer to sec. 25 only, obliterating  
the scribe marks on the SE. bearing tree.

Alongside of old stone cor.,

Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 25 only, with  
brass cap marked,

$\frac{1}{4}$  S25 |  
1928

from which

A fir, 24 ins. diam., bears S.68\*E., 25 lks. dist.

Marked  $\frac{1}{4}$  S 30 B T (old B. T.)

A hemlock, 12 ins. diam., bears S.66\*W., 130 lks.

Marked  $\frac{1}{4}$  S 25 B T.

A cedar, 30 ins. diam., bears N.70\*W., (not N.78\*W.)

25 lks. dist., marked  $\frac{1}{4}$  S 25 B T (old B. T.)