

Dependent Resurvey of the Willamette Meridian
through T. 26 S.

CHAINS


Thence,

N.0°30'E.

Ascend 220 ft. over broken SW. slope.

6.26 Point for the $\frac{1}{4}$ sec. cor. of sec. 30 only, later determined.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 30 only, with brass cap marked,



from which

A fir, 20 ins. diam., bears N.31°E., 62 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.

A fir, 20 ins. diam., bears S.20°E., 29 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.


22.20 Spur, slopes W. Descend 173 ft. over NW. slope.

39.82 Intersect the cor., established for secs. 19, 24, 25 and 30 which is a basalt stone, 10x7x5 ins. above ground, marked with 4 notches on the N. and 2 notches on the S. edge.

I change this cor. to refer to secs. 24 and 25 only, obliterating the scribe marks on the NE. and SE. bearing trees.

Alongside of old stone cor,

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 24 and 25 only, with brass cap marked,



from which the original bearing trees,

A hemlock, 20 ins. diam., bears N.44°E., 41 lks.

Marked T 26 S R 1 E S 19 B T.