

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian  
through T. 26 S.

CHAINS	
	<p>marked with 3 notches on the N. and 3 notches on the S. edge.</p> <p>I change this cor. to refer to secs. 13 and 24 only, obliterating the scribe marks on the NE. and SE. bearing trees, from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N.30<math>\frac{1}{2}</math>*E., 87 lks. dist. Marked T 26 S R 1 E S 18 B T ( old B. T. )</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears S.83<math>\frac{1}{4}</math>*E., 83 lks. Marked T 26 S R 1 E S 19 B T (old B. T. )</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S.87*W., 83 lks. dist. (not 100 lks.) Marked T 26 S R 1 W S 24 B T ( old B. T. )</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N.51*W., 211 lks. dist. ( not N.47*W., 205 lks. ) Marked T 26 S R 1 W S 13 B T ( old B. T. )</p> <p>Land, mountainous.</p> <p>Soil, loam and rocky, third rate.</p> <p>Timber, fir and hemlock.</p> <p>Undergrowth, lilac, arrowwood and vine maple.</p>
	<p>N.2*13'E., resurveying the E. bdy. of sec. 13.</p> <p>Over mountainous land, through timber and brush.</p> <p>Ascend 78 ft. over SW. slope.</p>
2.20	<p>Spur, slopes NW.</p> <p>Descend 532 ft. over N. slope.</p>
5.35	<p>Point for the closing cor. of secs. 18 and 19, later determined and hereinafter described.</p>
13.40	<p>Draw, course NE.</p> <p>Ascend 120 ft. over bluffs on SW. slope.</p>
16.70	<p>Point of a rocky spur, slopes NW.</p> <p>Descend 130 ft. over bluffs on NW. slope.</p>
24.40	<p>Creek, 2 lks. wide, course W.</p> <p>Ascend 525 ft. over broken SW. slope.</p>
41.67	<p>Intersect the old witness <math>\frac{1}{4}</math> sec. cor., established for secs. 13 and 18, which is a basalt stone in place,</p>