

Dependent Resurvey of the Willamette Meridian
through T. 26 S.


CHAINS

36.87 Intersect the old cor., established for secs. 7, 12, 13 and 18, which is a point determined from three of the original bearing trees.

This cor. will hereafter refer to secs. 12 and 13 only.

At exact cor. point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for the cor. of secs. 12 and 13 only, with brass cap marked,



from which

A fir, 16 ins. diam., bears N, 39 1/2 *E., 74 lks. dist.

Marked T 26 S R 1 E S 7 B T (destroy marks).

A fir, 6 ins. diam., bears S. 68 *E., 28 lks. dist.

Marked T 26 S R 1 E S 18 B T (destroy marks).

No trace of old SW. bearing tree.

A fir stump, 12 ins. diam., bears N. 8 *W., 40 lks.

Marked T 26 S R 1 W S 12 B T (old B. T.)

Raise a mound of stone with a 4 ft. base, 2 ft. high

S. 40 *W., 10 lks. dist., from cor., as no bearing trees were available and the ground was too steep to raise the mound of stone W. of cor.

Land, mountainous.

Soil, loam and rocky, third rate.

Timber, fir and hemlock.

Undergrowth, lilac and vine maple.

1.90 Spur, slopes W.

Descend 876 ft. over broken NW. slope.

6.85 Point for the closing cor. of secs. 7 and 18 later determined and hereinafter described.